QUOTATION

Sub:- Providing power points and AC points & other associated work in aluminium partition room at Imagineering lab Central workshop near academic gate no-4.

| S. No | D. DESCRIPTION | QTY | UNIT | RATE (In words & Figures) | AMOUNT |
|-------|---|-------|-------|---------------------------|--------|
| 1 | Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with modular switch, modular plate, suitable Gl box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required. | | | (III words & rigures) | |
| a | Group C | 4.00 | Point | | |
| 2 | Supplying and drawing following sizes of FRLS PVC insulated copper conductor, single core cable in the existing surface/ recessed steel/ PVC conduit as required. | | | | £ |
| a | 3 x 1.5 sq. mm | 50.00 | Metre | | |
| b | 3 x 2.5 sq. mm | 20.00 | Metre | | |
| C | 3 x 4 sq. mm | 45.00 | Metre | | |
| d | 3 x 10 sq.mm. | 25.00 | Meter | | |
| 3 | Supply and fixing of 105 x 50 mm DLP trunking white-system but without cover and partion etc. as required complete. | 25.00 | Meter | | |
| 4 | Supply and fixing of following accessories suitable for 105 mm x 50 mm size plastic trunking white system. | | | | |
| a | 85 mm flexible cover | 20.00 | Meter | | |
| b | End cap | 5.00 | Nos. | | |
| C | Internal angles- adjustable from 80°-100° | 2.00 | Nos. | | |
| d | external angles- adjustable from 60°-120° | 1.00 | Nos. | | |
| e | flat angles | 2.00 | Nos. | | |

| S. N | . No. DESCRIPTION | | UNIT | RATE | AMOUNT |
|------|--|------|------|----------------------|--------|
| 162 | | | | (In words & Figures) | |
| 5 | Supplying and fixing following way, single pole and neutral, sheet steel, MCB distribution board, 240 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator) | | | | |
| a | 8 way , Double door | 1.00 | No. | | |
| 6 | Supplying and fixing following rating, 240/415 V, 10 kA, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. | | | | |
| a | Single pole 5 A to 32 A | 8.00 | No. | | |
| b | Double pole 5 A to 32 A | 1.00 | No. | | |
| 7 | Supplying and fixing 20 A, 240 V, SPN Industrial type socket outlet, with 2 pole and earth, metal enclosed plug top alongwith 20 A "C" curve, SP, MCB, in sheet steel enclosure, on surface or in recess, with chained metal cover for the socket out let and complete with connections, testing and commissioning etc. as required. | 1.00 | No. | | |
| 8 | Supplying and fixing following modular switch/ socket on the existing modular plate & switch box including connections but excluding modular plate etc. as required. | | | | |
| a | 5/6 A switch | 2.00 | No. | | |
| b | 15/16 A switch | 6.00 | No. | | |
| C | 3 pin 5/6 A socket outlet | 4.00 | No. | | |
| d | 6 pin 15/16 A socket outlet | 6.00 | No. | | |
| 9 | Supplying and fixing two module stepped type electronic fan regulator on the existing modular plate switch box including connections but excluding modular plate etc. as required. | 4.00 | No. | | |

| S. No | S. No. DESCRIPTION | | UNIT | RATE | AMOUNT |
|-------|---|------|------|----------------------|--------|
| | | | | (In words & Figures) | |
| 10 | Supplying and fixing following Modular base & cover plate on existing modular metal boxes etc. as required. | | | | |
| a | 3 Module | 2.00 | No. | | |
| b | 4 Module | 7.00 | No. | | |
| C | 6 Module | 1.00 | No. | | |
| d | 8 Module | 1.00 | No. | | |
| 11 | Supply and fixing of following LED light fixture with Electronic driver, LED lamp, reflector, diffusser, MS body/housing holder etc. complete with all fixing accessories and lamp as required complete. | | | | |
| a | 36 watt recess mounting LED light fixture 600 x 600 mm | 2.00 | Nos. | | |
| 12 | Supply Installation, testing and commissioning of following ceiling fan, including wiring the down rods of standard length (upto 30 cm) with 1.5 sq. mm FR PVC insulated, copper conductor, single core cable etc. as required. | | | | |
| a | 1400 mm sweep | 1.00 | Nos. | | |
| | Say Rs. | | | | ^ |