## QUOTATION

Providing power points and light points for seprate location to install Bam fall Hammer instrument near old sac, Block-A.

	instrument near old sac, Block-A.			DATE	AMOUNT
SL No.	DESCRIPTION	QUANTITY	UNIT	RATE (In words & Figures)	AMOUNT
1	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed steel conduit, with modular switch, modular plate, suitable Gl box and earthing the point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable etc. as required.	e E			
а	Group C	3.00	Point		
2	Supplying and drawing following sizes of FRLS PVC insulated copper conductor, single core cable in the existing surface/ recessed steel/ PVC conduit a required.	e			
a	3 x 1.5 sq. mm	5.00	Metre		
b	3 x 2.5 sq. mm	10.00	Metre		
c	3 x 4 sq. mm	8.00	Metre		
3	Supplying and fixing following modular switch socket on the existing modular plate & switch be including connections but excluding modular platect. as required.	OX			
a	5/6 A switch	4.00	No.		
b	3 pin 5/6 A socket outlet	4.00	No.		
4	Supplying and fixing following size/ modules, Gl by alongwith modular base & cover plate for module switches in recess etc. as required.	ox lar			
а	3 Module (100mmX75mm)	4.00	No.		
5	neutral, sheet steel, MCB distribution board, 240 on surface/ recess, complete with tinned copper by	V, bus par, ing			
	a 8 way, Double door	1.00	No.		

SL No.	DESCRIPTION	QUANTITY	UNIT	RATE
At				(In words & Figures)
6	Supplying and fixing following rating, 240/415 V, 10 kA, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required.	**************************************	<i>r</i>	
a	Single pole 5 A to 32 A	8.00	No.	
b	Double pole 5 A to 32 A	1.00	No.	
7	Supplying and fixing 20 A, 240 V, SPN Industrial type socket outlet, with 2 pole and earth, metal enclosed plug top alongwith 20 A "C" curve, SP, MCB, in sheet steel enclosure, on surface or in recess, with chained metal cover for the socket out let and complete with connections, testing and commissioning etc. as required.		No.	
8	Providing and fixing 25 mm X 5 mm G.l. strip on surface or in recess for connections etc. as required.	10.00	Metre	
9.00	Chemical Earthing with GI earth electrode 50mm dia x 3 mtr length including earth enhancing compound (Jam Fill quality product) and PIT cover for earthing pit etc as reqd.		No.	
10.00	Supply and fixing of 32 x 20 mm DLP mini- trunking white-system with independent cover etc. as required complete.		Meter	
11.00	Supply and fixing of following accessories suitable for 32 mm x 20 mm size plastic trunking white			
a	system. End cap	2.00	Nos.	
b	internal / external angle	2.00	Nos.	
c	changeable flat angle	1.00	Nos.	
12.00	Supply and fixing of following LED light fixture with efficiency >100 lumen/ watt, P.F. >0.95, THD<10%, Electronic driver, LED lamp, reflector, diffusser, MS body/housing holder etc. complete with all fixing accessories and lamp as required complete.	•		
a	36 watt recess mounting LED light fixture 600 x 600 mm	2.00	Nos.	
13.00	Supplying and fixing exhaust fan shutter for following sizes exhaust fan on rag bolts as reqd complete.			
a	for 375 mm / 15" sweep	1.00	Nos.	

AMOUNT

SL No.	DESCRIPTION	QUANTITY	UNIT	RATE	AMOUNT	
				(In words & Figures)		
14.00	Supplying and laying of one no. 2 x 10.0 sqmr insulated, XLPE steel armoured aluminium corpower cable of grade 1.1 kV as required comp following manners.	nductor				
a	in ground I/c excavation, sand caushioning, protective covering and refixing the trench etc a	as reqd	12.00	Meter		
b	On Surface		18.00	Meter		
15.00	Supply, Installation testing and commission following seep, copper wound, 900 RPM, 22 AC, 50 Hz exhaust fan in the existing opening required complete.	20 volt				
a	375 mm / 15" sweep		1.00	Nos.		

Total Rs.

अधिनारी अभिग्ना कि।/इ.ह. (१९७४.) संदर्भकारित, यात जीत संस्थान, स्थानुर I.W.D., I.I.T. Kamprott